

Material Safety Data Sheet

1. MATERIAL AND COMPANY IDENTIFICATION

Material Name : Ultra Low Sulfur Diesel Fuel 2 (S-15 ppm) Dyed
Uses : Fuel for on-road diesel-powered engines.
Company : Motiva Enterprises LLC
 P.O. Box 4540
 Houston, TX 77210-4540
 United States

MSDS Request : 877-276-7285

Emergency Telephone Number
Spill Information : 877-242-7400
Health Information : 877-504-9351

2. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	Concentration
Fuels, diesel, no.2	68476-34-6	100.00 %

Dyes and markers can be used to indicate tax status and prevent fraud.
 Contains/may contain full range straight run middle distillate.
 Contains/may contain light catalytic cracked distillate.
 Contains/may contain hydrotreated middle distillate.

3. HAZARDS IDENTIFICATION

Emergency Overview	
Appearance and Odour	: Clear, bright liquid. Hydrocarbon.
Health Hazards	: Harmful: may cause lung damage if swallowed. Vapours may cause drowsiness and dizziness.
Safety Hazards	: Combustible liquid. Electrostatic charges may be generated during pumping. Electrostatic discharge may cause fire.
Environmental Hazards	: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Health Hazards

Inhalation : Slightly irritating to respiratory system. Breathing of high vapour concentrations may cause central nervous system (CNS) depression resulting in dizziness, light-headedness, headache and nausea.

Skin Contact : May cause moderate irritation to skin. Repeated exposure may cause skin dryness or cracking.

Eye Contact : May cause slight irritation to eyes.

Ingestion : Harmful: may cause lung damage if swallowed.

Other Information : Limited evidence of carcinogenic effect.

Signs and Symptoms : If material enters lungs, signs and symptoms may include coughing, choking, wheezing, difficulty in breathing, chest congestion, shortness of breath, and/or fever. The onset of

Material Safety Data Sheet

- respiratory symptoms may be delayed for several hours after exposure.
- Defatting dermatitis signs and symptoms may include a burning sensation and/or a dried/cracked appearance.
- Skin irritation signs and symptoms may include a burning sensation, redness, swelling, and/or blisters.
- Aggravated Medical Condition** : Pre-existing medical conditions of the following organ(s) or organ system(s) may be aggravated by exposure to this material: Skin.
- Environmental Hazards** : Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- Additional Information** : This product is intended for use in closed systems only.

4. FIRST AID MEASURES

- Inhalation** : Remove to fresh air. If rapid recovery does not occur, transport to nearest medical facility for additional treatment.
- Skin Contact** : Remove contaminated clothing. Immediately flush skin with large amounts of water for at least 15 minutes, and follow by washing with soap and water if available. If redness, swelling, pain and/or blisters occur, transport to the nearest medical facility for additional treatment.
- Eye Contact** : Flush eye with copious quantities of water. If persistent irritation occurs, obtain medical attention.
- Ingestion** : If swallowed, do not induce vomiting; transport to nearest medical facility for additional treatment. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. If any of the following delayed signs and symptoms appear within the next 6 hours, transport to the nearest medical facility: fever greater than 101° F (37° C), shortness of breath, chest congestion or continued coughing or wheezing.
- Advice to Physician** : Treat symptomatically. Potential for chemical pneumonitis. Consider: gastric lavage with protected airway, administration of activated charcoal. Administration of carbon for medicinal use (carbo medicinalis) may reduce absorption from the digestive tract.

5. FIRE FIGHTING MEASURES

Clear fire area of all non-emergency personnel.

- Flash point** : > 52 °C / 126 °F
- Explosion / Flammability limits in air** : 0.5 - 4.4 %(V)
- Auto ignition temperature** : 260 °C / 500 °F
- Specific Hazards** : Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Oxides of sulphur. Unidentified organic and inorganic compounds. Carbon monoxide may be evolved if incomplete combustion occurs. Will float and can be reignited on surface water. Flammable vapours may be present even at temperatures below the flash point.

Material Safety Data Sheet

- Extinguishing Media** : Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
- Unsuitable Extinguishing Media** : Do not use water in a jet.
- Protective Equipment for Firefighters** : Wear full protective clothing and self-contained breathing apparatus.
- Additional Advice** : Keep adjacent containers cool by spraying with water.

6. ACCIDENTAL RELEASE MEASURES

Avoid contact with spilled or released material. For guidance on selection of personal protective equipment see Chapter 8 of this Material Safety Data Sheet. See Chapter 13 for information on disposal. Observe all relevant local and international regulations. Evacuate the area of all non-essential personnel. Ventilate contaminated area thoroughly.

- Protective measures** : Do not breathe fumes, vapour. Do not operate electrical equipment. Shut off leaks, if possible without personal risks. Remove all possible sources of ignition in the surrounding area. Use appropriate containment (of product and fire fighting water) to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers. Attempt to disperse the vapour or to direct its flow to a safe location for example by using fog sprays. Take precautionary measures against static discharge. Ensure electrical continuity by bonding and grounding (earthing) all equipment.
- Clean Up Methods** : For small liquid spills (< 1 drum), transfer by mechanical means to a labelled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely. For large liquid spills (> 1 drum), transfer by mechanical means such as vacuum truck to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely. Shovel into a suitable clearly marked container for disposal or reclamation in accordance with local regulations.
- Additional Advice** : Notify authorities if any exposure to the general public or the environment occurs or is likely to occur. Local authorities should be advised if significant spillages cannot be contained. Maritime spillages should be dealt with using a Shipboard Oil Pollution Emergency Plan (SOPEP), as required by MARPOL Annex 1 Regulation 26. U.S. regulations may require reporting releases of this material to the environment which exceed the reportable quantity (refer to Chapter 15) to the National Response Centre at (800) 424-8802. Under Section 311 of the Clean Water Act (CWA) this material is considered an oil. As such, spills into surface waters must be reported to the National Response Centre at (800) 424-8802. This material is covered by EPA's Comprehensive Environmental Response,

Material Safety Data Sheet

Compensation and Liability Act (CERCLA) Petroleum Exclusion. Therefore, releases to the environment may not be reportable under CERCLA.

7. HANDLING AND STORAGE

- General Precautions** : Avoid breathing vapours or contact with material. Only use in well ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment see Chapter 8 of this Material Safety Data Sheet. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material. Air-dry contaminated clothing in a well-ventilated area before laundering. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires. Prevent spillages. Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols. Never siphon by mouth. Contaminated leather articles including shoes cannot be decontaminated and should be destroyed to prevent reuse. For comprehensive advice on handling, product transfer, storage and tank cleaning refer to the product supplier.
- Handling** : Avoid inhaling vapour and/or mists. Avoid prolonged or repeated contact with skin. When using do not eat or drink. Extinguish any naked flames. Do not smoke. Remove ignition sources. Avoid sparks. Earth all equipment. Electrostatic charges may be generated during pumping. Electrostatic discharge may cause fire. Not expected to be a health hazard when used under normal conditions.
- Storage** : Drum and small container storage: Drums should be stacked to a maximum of 3 high. Use properly labelled and closeable containers. Tank storage: Tanks must be specifically designed for use with this product. Bulk storage tanks should be diked (bunded). Locate tanks away from heat and other sources of ignition. Must be stored in a diked (bunded) well-ventilated area, away from sunlight, ignition sources and other sources of heat. Vapours from tanks should not be released to atmosphere. Breathing losses during storage should be controlled by a suitable vapour treatment system. The vapour is heavier than air. Beware of accumulation in pits and confined spaces.
- Product Transfer** : Avoid splash filling. Wait 2 minutes after tank filling (for tanks such as those on road tanker vehicles) before opening hatches or manholes. Wait 30 minutes after tank filling (for large storage tanks) before opening hatches or manholes. Keep containers closed when not in use. Do not use compressed air for filling, discharging or handling. Contamination resulting from product transfer may give rise to light hydrocarbon vapour in the headspace of tanks that have previously contained gasoline. This vapour may explode if there is a source of ignition. Partly filled containers present a greater hazard than those that are full, therefore handling, transfer and sampling

Material Safety Data Sheet

- Container Advice** : activities need special care.
: Containers, even those that have been emptied, can contain explosive vapours. Do not cut, drill, grind, weld or perform similar operations on or near containers.
- Additional Information** : Ensure that all local regulations regarding handling and storage facilities are followed.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Occupational Exposure Limits**

Material	Source	Type	ppm	mg/m3	Notation
Fuels, diesel, no.2	ACGIH	TWA(Vapor and aerosol.)		100 mg/m3	as total hydrocarbons
Fuels, diesel, no.2	ACGIH	SKIN_DES(Vapor and aerosol.)			Can be absorbed through the skin.as total hydrocarbons

- Additional Information** : In the absence of a national exposure limit, the American Conference of Governmental Industrial Hygienists (ACGIH) recommends the following values for Diesel Fuel: TWA - 100 mg/m3 Critical effects based on Skin and Irritation. Skin notation means that significant exposure can also occur by absorption of liquid through the skin and of vapour through the eyes or mucous membranes. Shell has adopted as Interim Standards the OSHA Z1A values that were established in 1989 and later rescinded.
- Exposure Controls** : The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include: Use sealed systems as far as possible. Adequate ventilation to control airborne concentrations below the exposure guidelines/limits. Local exhaust ventilation is recommended. Eye washes and showers for emergency use.
- Personal Protective Equipment** : Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.
- Respiratory Protection** : If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are unsuitable (e.g., airborne concentrations are high, risk of oxygen deficiency, confined space) use appropriate positive pressure breathing apparatus. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. All respiratory protection equipment and use must be in accordance with local regulations. Respirator selection, use and maintenance should be in

Material Safety Data Sheet

Hand Protection

accordance with the requirements of the OSHA Respiratory Protection Standard, 29 CFR 1910.134.

- : Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced.
- : Chemical splash goggles (chemical monogoggles).
- : Chemical resistant gloves/gauntlets, boots, and apron (where risk of splashing).

Eye Protection

Protective Clothing

9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : Clear, bright liquid.
- Odour : Hydrocarbon.
- Flash point : > 52 °C / 126 °F
- Explosion / Flammability limits in air : 0.5 - 4.4 %(V)
- Auto-ignition temperature : 260 °C / 500 °F
- Specific gravity : 0.85

10. STABILITY AND REACTIVITY

- Stability** : Stable under normal conditions of use.
- Conditions to Avoid** : Avoid heat, sparks, open flames and other ignition sources.
- Materials to Avoid** : Strong oxidising agents.
- Hazardous Decomposition Products** : Hazardous decomposition products are not expected to form during normal storage.
Thermal decomposition is highly dependent on conditions. A complex mixture of airborne solids, liquids and gases, including carbon monoxide, carbon dioxide and other organic compounds will be evolved when this material undergoes combustion or thermal or oxidative degradation.

11. TOXICOLOGICAL INFORMATION

- Basis for Assessment** : Information given is based on product data, a knowledge of the components and the toxicology of similar products.
- Acute Oral Toxicity** : Low toxicity: LD50 >2000 mg/kg , Rat
Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.
- Acute Dermal Toxicity** : Low toxicity: LD50 >2000 mg/kg , Rabbit
- Acute Inhalation Toxicity** : Low toxicity: LC50 >20 mg/l / 1.00 h, Rat
High concentrations may cause central nervous system depression resulting in headaches, dizziness and nausea; continued inhalation may result in unconsciousness and/or death.
- Skin Irritation** : May cause moderate skin irritation (but insufficient to classify).
Prolonged/repeated contact may cause defatting of the skin

Material Safety Data Sheet

- which can lead to dermatitis.
- Eye Irritation** : Slightly irritating.
- Respiratory Irritation** : Slightly irritating.
- Sensitisation** : Not a skin sensitiser.
- Repeated Dose Toxicity** : Kidney: caused kidney effects in male rats which are not considered relevant to humans
- Mutagenicity** : Mutagenic; positive in in-vivo and in-vitro assays.
- Carcinogenicity** : Limited evidence of carcinogenic effect.
Repeated skin contact has resulted in irritation and skin cancer in animals.

Material	: Carcinogenicity Classification
Fuels, diesel, no.2	: ACGIH Group A3: Confirmed animal carcinogen with unknown relevance to humans.
Distillates (petroleum), light catalytic cracked	: IARC 2A: Probable carcinogen.

- Reproductive and Developmental Toxicity** : Not expected to be a developmental toxicant.

12. ECOLOGICAL INFORMATION

Information given is based on a knowledge of the components and the ecotoxicology of similar products. Fuels are typically made from blending several refinery streams. Ecotoxicological studies have been carried out on a variety of hydrocarbon blends and streams but not those containing additives.

- Acute Toxicity** : Toxic: LL/EL/IL50 1-10 mg/l (to aquatic organisms) (LL/EL50 expressed as the nominal amount of product required to prepare aqueous test extract).
- Mobility** : Floats on water. Partly evaporates from water or soil surfaces, but a significant proportion will remain after one day. Large volumes may penetrate soil and could contaminate groundwater. Contains volatile constituents.
- Persistence/degradability** : Major constituents are inherently biodegradable. The volatile constituents will oxidize rapidly by photochemical reactions in air.
- Bioaccumulation** : Contains constituents with the potential to bioaccumulate.
- Other Adverse Effects** : Films formed on water may affect oxygen transfer and damage organisms.

13. DISPOSAL CONSIDERATIONS

- Material Disposal** : Recover or recycle if possible. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations. Do not dispose into the environment, in drains or in water courses. Do not dispose of tank water bottoms by allowing them to drain into the ground. This will result in soil and groundwater contamination. Waste arising

Material Safety Data Sheet**Container Disposal**

from a spillage or tank cleaning should be disposed of in accordance with prevailing regulations, preferably to a recognised collector or contractor. The competence of the collector or contractor should be established beforehand.

: Send to drum recoverer or metal reclaimer. Drain container thoroughly. After draining, vent in a safe place away from sparks and fire. Residues may cause an explosion hazard if heated above the flash point. Do not puncture, cut or weld uncleaned drums. Do not pollute the soil, water or environment with the waste container. Comply with any local recovery or waste disposal regulations.

Local Legislation

: Disposal should be in accordance with applicable regional, national, and local laws and regulations. Local regulations may be more stringent than regional or national requirements and must be complied with.

14. TRANSPORT INFORMATION**US Department of Transportation Classification (49CFR)**

Identification number	NA 1993
Proper shipping name	Diesel Fuel
Class / Division	Combustible liquid
Packing group	III

Emergency Response Guide No.	128
------------------------------	-----

Additional Information Oil: This product is an oil under 49CFR (DOT) Part 130. If shipped by rail or highway in a tank with a capacity of 3500 gallons or more, it is subject to these requirements. Mixtures or solutions containing 10% or more of this product may also be subject to this rule.

IMDG

Identification number	UN 1202
Proper shipping name	DIESEL FUEL
Class / Division	3
Packing group	III
Marine pollutant:	No

IATA (Country variations may apply)

Identification number	UN 1202
Proper shipping name	Diesel fuel
Class / Division	3
Packing group	III

15. REGULATORY INFORMATION

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

Federal Regulatory Status

Material Safety Data Sheet

Ultra Low Sulfur Diesel Fuel 2 (S-15 ppm) Dyed ()

Shell classifies this material as an "oil" under the CERCLA Petroleum Exclusion, therefore releases to the environment are not reportable under CERCLA.

Under Section 311 of the Clean Water Act (CWA) this material is considered an oil. As such, spills into surface waters must be reported to the National Response Centre at (800) 424-8802.

SARA Hazard Categories (311/312)

Immediate (Acute) Health Hazard. Delayed (Chronic) Health Hazard. Fire Hazard.

State Regulatory Status

California Safe Drinking Water and Toxic Enforcement Act (Proposition 65)

This material does not contain any chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

Pennsylvania Right-To-Know Chemical List

Fuels, diesel, no.2 (68476-34-6) 100.00% Listed.

16. OTHER INFORMATION

- Additional Information** : This document contains important information to ensure the safe storage, handling and use of this product. The information in this document should be brought to the attention of the person in your organisation responsible for advising on safety matters.
- NFPA Rating (Health, Fire, Reactivity)** : 2, 2, 0
- MSDS Version Number** : 4.
- MSDS Effective Date** : 06/16/2007
- MSDS Revisions** : A vertical bar (|) in the left margin indicates an amendment from the previous version.
- MSDS Regulation** : The content and format of this MSDS is in accordance with the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
- MSDS Distribution** : The information in this document should be made available to all who may handle the product.
- Disclaimer** : The information contained herein is based on our current knowledge of the underlying data and is intended to describe

Material Safety Data Sheet

Ultra Low Sulfur Diesel Fuel 2 (S-15 ppm) Dyed

MSDS# 401398MU

Version 4.

Effective Date 06/16/2007

According to OSHA Hazard Communication Standard, 29 CFR
1910.1200

the product for the purpose of health, safety and environmental requirements only. No warranty or guarantee is expressed or implied regarding the accuracy of these data or the results to be obtained from the use of the product.